



UK Declaration of Performance: 097-00044-00

1. Unique identification code of the product-type:

A13

A14

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Serial number examples:

06A#####

06C#####

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Self-contained smoke and CO alarm for use in single and multi family dwellings

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Google LLC, 1600 Amphitheatre Parkway, Mountain View, CA 94043

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not Applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

UL International (UK) Ltd.

Unit 1 - 3 Horizon, Kingsland Business Park, Wade Road, Basingstoke, Hampshire, RG24 8AH

performed type testing and the initial inspection of the manufacturing plant and of factory production control with continuous surveillance, assessment and approval of the factory production control under system 1 and issued following certificate of constancy of performance:

0843-CPR-1014 for A14, 0843-CPR-1013 for A13

8. In case of the declaration of performance concerning a construction product for which a UK Technical Assessment has been issued:

Not applicable, see item 7

9. Declared performance:

All requirements including all Essential Characteristics and the corresponding performances for the intended use or uses indicated in 3. have been determined as described in the designated standards mentioned in the following table.

Essential Characteristics	Performance	Designated Technical Specification
	Models A13, A14	EN 14604:2005 + AC1:2008
Nominal activation conditions/ Sensitivity, Response delay (response time) and Performance under fire condition	Pass	4.12, 4.18, 5.2, 5.3, 5.4, 5.5, 5.6, 5.15, 5.17, 5.18, 5.19, 5.20
Operational reliability	Pass	4.1, 4.2, 4.3, 4.4, 4.5, 4.6, 4.7, 4.8, 4.9, 4.10, 4.11, 4.13, 4.14, 4.15, 4.16, 4.17, 4.19, 5.11, 5.16, 5.22, 5.23, 5.24
Tolerance to supply voltage	Pass	5.21
Durability of operational reliability and response delay, temperature resistance	Pass	5.7, 5.8
Durability of operational reliability, vibration resistance	Pass	5.12, 5.13
Durability of operational reliability, humidity resistance	Pass	5.9
Durability of operational reliability, corrosion resistance	Pass	5.10
Durability of operational reliability, electrical stability	Pass	5.14

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

DocuSigned by:



9B9A308CC0524BF...
Signature

Date of issue: 8 Nov, 2021 in Mountain View, CA, USA

Ajay Kamath
Senior Director, Product Integrity Engineering